

Restaurant Details- PopUp Bagels (20240325010002)

Food Service Establishment Permit(FSEP)

FSEP#: [REDACTED]

Expiration Date: 03/31/2025

DOHMH Status: CURRENT

Business Legal Name: POPUP BAGELS INC

Assumed Name: PopUp Bagels

Business Address: 177 THOMPSON ST, NEW YORK, NY 10012

Venue Type: Bakery

Last updated from DOHMH: 11/12/2024

Restaurant Information

Phone: [REDACTED]

Email Address: [REDACTED]

DOS Information

DOS ID#: [REDACTED]

Process Name: Popupbagels Inc.

DOS Address: [REDACTED]

NYS Liquor Authority Information

Establishment serves alcohol : No

User Information

Created By: Rachel Golan

Created On: 3/20/2024 12:28:39 PM

Modified By: Rachel Golan

Modified On: 5/3/2024 11:00:05 AM

Business hours

Sun: 7:00 AM- 2:00 PM

Mon: 7:00 AM- 2:00 PM

Tues: 7:00 AM- 2:00 PM

Wed: 7:00 AM- 2:00 PM

Thurs: 7:00 AM- 2:00 PM

Fri: 7:00 AM- 2:00 PM

Sat: 7:00 AM- 2:00 PM

Site Photos- PopUp Bagels (20240325010002)













FDNY

www.nyc.gov/fdny
KEVIN F. WOODS
Chief of Operations
Bureau of Operations

October 31, 2024

NYC Department of Transportation
Attn: Ms. Lauren Antonelli
55 Water Street
New York, NY 10041

Re: **Establishment Reviewed:** PopUp Bagel
177 Thompson Street
Manhattan, NY 10012

Introduction

The Roadway Café would be situated on the west side of Thompson Street, due north of W. Houston Street.

Per NYCDOT:

- The roadway is approximately 26' wide (curb to curb).
 - The applicant is proposing a structure that is 6' wide.
 - If implemented, the emergency travel lane remaining would be 12 feet wide.

Findings

FDNY City Planning issued a memo titled 'NYCDOT's Dining Out NYC Program', dated 7.30.24, which provides recommended safety practices. The proposed Roadway Café is not in compliance as outlined:

<u>Criteria from memo: NYCDOT's Dining Out NYC Program:</u>	<u>FDNY City Planning Comments</u>
1.1 The FDNY does not encourage the implementation of such variances (Roadway Cafés that propose reducing the emergency travel lane width to less than 15'.	The proposed Roadway Café would reduce the emergency travel lane to 12'.

Challenges to Firefighting Operational Protocols

The proposed Roadway Café presents an obstruction having potential to negatively impact Fire Operations. However, the FDNY Bureau of Operations has determined the potential impact as minimal, and therefore, with coordination with local units, has **no objection** to implementation.

Applicant is required to contact Battalion 6, Engine 33, Ladder 9, (bat006@fdny.nyc.gov, eng033@fdny.nyc.gov, lad035@fdny.nyc.gov) prior to occupancy of the Roadway Café to provide familiarization. Considerations offered by the Administrative Company shall be applied to the approved Roadway Café as deemed necessary.

Very truly yours,


Kevin F. Woods
Chief of Operations

10.24.24 (b)

SECTION 1: Site Plan



- This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application.
- Refer to the [How to Apply](#) page in the Dining Out NYC website for more information about the application process.

Roadway Cafe Site Plan Form


Identify Permitted Parking Location:

- Identify the Parking Sign in front of or around the area where your roadway setup would be located.
- Roadway cafes can only be placed in:
 - Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking, and seasonally restricted parking.
 - Loading areas, including loading only, truck loading, hotel loading, and no parking zones.
 - Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curb.

- P1- Parking Space
- P2- Loading Area
- P3- Floating Parking Lane

Applicant Name: Jamie Lissette
 Restaurant Name: PopUp Bagels, Inc
 FSEP Number: 50134151

Use the space below to draw or upload your Site Plan representing your cafe perimeters, furniture, and clearances.



Length of roadway cafe: 6.5 feet Width of roadway cafe: 8 feet

Drawing Requirements

Food service establishment frontage shown as:

- Line representing the establishment's space facing the sidewalk
- Length
- Label

Street names:

- Labels on each street

Sidewalk shown as:

- Line representing street curb

Roadway shown as:

- Width of curbside lane

Cafe perimeter shown as:

- Lines indicating perimeter
- Length and width

Set-up furniture (tables, chairs, etc.) shown as:

- Lines or symbols at approximate location within setup

Elements (in Section 2 of this form) within 15 feet of cafe perimeter, shown as:

- Lines or symbols
- Distance from cafe perimeter
- Labels

Utility coverings (water/gas valves, and pull boxes) shown as:

- Symbols representing the location within the setup

North arrow

SECTION 2: Required Clearances

- Please provide distances from the following objects.
- Only provide a distance if the listed object is within 15 feet of your proposed setup.
- Refer to the [Dining Out NYC website](#) for more information regarding clearances.

Elements with minimum 15 feet clearance from roadway cafe:

R01- Subway Stair: Open End _____ feet R02- Fire Hydrant _____ feet

Elements with minimum 10 feet clearance from roadway cafe:

R03- Subway Elevator Entrance _____ feet R05- MTA Curb Cut _____ feet

R04- FDNY Curb Cut _____ feet

Elements with minimum 5 feet clearance from roadway cafe:

R06- Curb Cut _____ feet R11- CitiBike/Bike Share Station _____ feet

R07- Emergency Exit Hatch _____ feet R12- Bike Corral _____ feet

R08- Subway Stair: Closed End _____ feet R13- Micromobility Station _____ feet

R09- Subway Elevator: Non-Entry _____ feet R14- Drainage Infrastructure _____ feet

R10- Bus Stop Pole:
Non- Approaching Side _____ feet

Elements with minimum 3 feet clearance from roadway cafe:

R15- Elevated Train Infrastructure _____ feet R16- Transformer Vault _____ feet

Elements with minimum 1 foot and 6 inches clearance from roadway cafe:

R17- Vent Infrastructure: utility vent poles, vent grates, subway grates _____ feet R18- Manholes _____ inches

Elements with minimum 6 inches clearance from roadway cafe:


R19- Thermoplastic Marking _____ feet

Roadway cafe distance from crosswalks:

R20- Adjacent to non-approaching side of crosswalk (min. 8 foot distance) _____ feet

R21- Adjacent to approaching (stopping) side of crosswalk (min. 20 foot distance) _____ feet

R22- No crosswalk present (maintain 20 feet from curb line of intersecting street) _____ feet



Check this box if none of the objects listed above are within 15 feet of the proposed setup.

SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the [Dining Out NYC website](#) for more information regarding materials.

Materials Checklist:

Required

Barriers (All of the following must be met)

- Maintained on all sides of the cafe except the side fronting the ground floor restaurant.
- Not permanently affixed to the roadway.
- 30-42 inches tall (excluding planting), and at least 4 inches in width.
- Barriers are interconnected with each other.
- Any cladding over the barriers is securely fastened or affixed.
- Minimum 4 inches wide reflective strip on each barrier on the outward facing side.
- Water-filled with a minimum of 150 pounds per linear foot of barrier length.

Optional - Only check the material categories you intend to use in your roadway cafe

Flooring (if using, all of the following must be met)

- Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
- Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements.
- Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.

Furnishings (if using, all of the following must be met)

- Lightweight and easily movable.

Vertical Screenings (if using, all of the following must be met)

- Located between the barrier and 6 feet above the cafe base or floor.
- Located on the roadway facing side, does not extend beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
- Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.
- If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

Overhead Coverings/ Umbrellas (if using, all of the following must be met)

- Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe.
- Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
- Easily removable, comprised of fire-grade and wind resistant materials.
- If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

Lighting and Electrical Connections (if using, all of the following must be met)

- Any lighting is outdoor rated, properly secured, and lightweight.
- At least 14 feet above sidewalk, and 18 feet above roadway.
- Not attached to any City property, including street trees.
- Electrical work complies with the applicable requirements set forth in DOT's rules and the New York City Electrical Code. Please note that this may require additional permits from DOB or FDNY, and/or approval from the Landmarks Preservation Commission (LPC) as applicable.