RESTAURANT DETAILS

Food Service Establishment Permit(FSEP)

FSEP#: 50104231

Expiration Date: 03/31/2026 DOHMH Status: CURRENT

Business Legal Name: BONDI - 75 KENMARE STREET, LLC

Assumed Name: BONDI SUSHI

Business Address: 75 KENMARE ST, NEW YORK, NY 10012

Venue Type: Restaurant (with bar)

Last updated from DOHMH: 07/07/2025

Restaurant Information

Entity Type: Limited Liability Corporation (LLC)

Phone:

Email Address:

DOS Information

DOS ID#: 5584633

Process Name: THE LLC, ATTN: JUSTIN HAUSER

DOS Address:

NYS Liquor Authority Information

NYSLA Serial No: 026723131230

License Type: On-Premises

Name of License: Bondi 75 Kenmare Street LLC

Title of Representative: Attorney

Name of Certificate Holder: David Hess

Business hours

Sun:

11:00 AM- 10:00 PM

Mon:

11:00 AM- 10:00 PM

Tues:

11:00 AM- 10:00 PM

Wed:

11:00 AM- 10:00 PM

Thurs:

11:00 AM- 10:00 PM


Fri:

11:00 AM- 10:00 PM


Sat:

11:00 AM- 10:00 PM









SECTION 1: Site Plan

- · This Site Plan form is required to be uploaded in the "Sidewalk Site Plan" field of your online application.
- Refer to the How to Apply page in the Dining Out NYC website for more information about the application process.

Length of sidewalk cafe: 28' + 41'

- Clear path requirement for your sidewalk cafe can be found by identifying your corridor type on the DOT's Pedestrian Mobility Plan Pedestrian Demand Map on Open Data. C1- Global Corridor (12 feet Clear Path) C2- Regional Corridor (10 feet Clear Path) C3- Neighborhood Corridor (8 feet Clear Path) C4- Community Connector (8 feet Clear Path) C5- Baseline Street (8 feet Clear Path)

Setup Area Identification:

- Please check this box if you plan to have outdoor dining located within private property. If so, indicate the property line in the site plan drawing below.
- Please check this box if all or part of your sidewalk cafe is in a sidewalk widening area, developed pursuant to the NYC Zoning Resolution. If so, indicate the property line in the site plan drawing below





Sidewalk Cafe Site Plan Form

Applicant Name:

Bondi - 75 Kenmare Street LLC.

Restaurant Name:

Bondi Sushi

FSEP Number:

50104231

Drawing Requirements

Food service establishment frontage shown by:

- Line representing space occupied in building
- Labels

Street names:

· Labels on each street

Sidewalk shown as:

- · Line representing street curb
- Width measured from building line to curb line

Primary building entrance shown as:

- Label
- Distance from proposed setup

Cafe perimeter shown as:

- Line
- · Length and width
- --- (Dashed line) representing Private Property Line

Set-up furniture (tables, chairs, etc.) shown as:

Lines or symbols at approximate location within setup


Sidewalk elements or objects shown as:


- Lines or symbols
- Labels
- Distance from cafe perimeter

Utility coverings shown as:

Symbols representing the approximate shape of the covering within the setup

MANHOLE COVER





Width of sidewalk cafe: 7'-10" + 3'-6" feet

SECTION 2: Required Clearances

- · Please provide distances from the following objects.
- Only provide a distance if the listed object is within 15 feet of your proposed setup.
- · Leave box blank if not applicable.
- Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding clearances.

Elements with minimum 15 feet of	clearance from sid	lewalk cafe:		
S01- Subway Stair: Open End	feet			
Elements with minimum 10 feet of	clearance from sid	lewalk cafe:		
S02- Subway Elevator Entrance	feet	S04- MTA Curb Cut	feet	
S03- Exhaust Duct	feet	S05- FDNY Curb Cut	feet	
Elements with minimum 8 feet clearance from sidewalk cafe:				
S06- Street Tree Bed	10 feet	S13- Newsstand	feet	
S07- Mailbox	feet	S14- Streetlight	10 feet	
S08- LinkNYC Kiosk	feet	S15- Bus Stop Pole	feet	
S09- Wayfinding Kiosk	feet	S16- Fire Hydrant	feet	
S10- E-charging Station	feet	S17- Bus Stop Shelter	feet	
S11- Parking Meter	feet	S18- Traffic Signal	feet	
S12- Select Bus Service Fare Machine	feet			
Elements with minimum 5 feet clearance from sidewalk cafe:				
S19- CitiBike/Bike Share Station	feet	S24- Emergency Exit Hatch	feet	
S20- Bike Corral	feet	S25- Subway Stair: Closed End	feet	
S21- Micromobility Station	feet	S26- Subway Elevator: Non-Entry	feet	
S22- Primary Building Entrance	feet	S27- Siamese Connection	feet	
S23- Curb Cut	feet			
Elements with minimum 3 feet clearance from sidewalk cafe:				
S28- Elevated Train Infrastructure	e feet			
S29- Transformer Vault	3 feet			
Elements with minimum 1 foot 6 inches clearance from sidewalk cafe elements:				
S30- Vent Infrastructure	inches			
Cannot block access		Cannot block or	· · · · · · · · · · · · · · · · · · ·	

escape stairs



- Please indicate which of the following materials will be part of your sidewalk cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements by checking the box next to the associated requirement.

#Required* Perimeter Demarcation Perimeter demarcation must be clear and visible by using a lightweight and removable self-supporting base wall, railing, planter, fence, or stanchion and rope. Maximum height is 2 feet 6 inches (excluding planting(s)). Not affixed to the sidewalk. *Optional- Only check the material categories you intend to use in your sidewalk cafe* Furnishings Lightweight and easily movable. Not affixed to the sidewalk. Awnings (Physically attached to the building) Minimum 8 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. Complies with the New York City Building Code and the requirements of the Landmarks Preservation Commission, as applicable. Overhead Coverings/ Umbrellas Minimum 7 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. The umbrella/overhead covering has a weighted base and any supports are not affixed to the sidewalk. Any support structures are of sufficient size and strength, made of durable materials, and free of defects Lighting and Electrical Connections Any lighting is outdoor rated, properly secured, and lightweight. Connection is directly connected to ground floor restaurant's power source and within the perimeter of the cafe. Does not exceed 10 feet in height. Not attached to any City property, including street trees. Electrical work complies with the applicable requirements set forth in the DOT's rules and the New York	 Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding materials. 				
Perimeter Demarcation Perimeter demarcation must be clear and visible by using a lightweight and removable self-supporting base wall, railing, planter, fence, or stanchion and rope. Maximum height is 2 feet 6 inches (excluding planting(s)). Not affixed to the sidewalk. *Optional- Only check the material categories you intend to use in your sidewalk cafe* Furnishings Lightweight and easily movable. Not affixed to the sidewalk. Awnings (Physically attached to the building) Minimum 8 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. Complies with the New York City Building Code and the requirements of the Landmarks Preservation Commission, as applicable. Overhead Coverings/ Umbrellas Minimum 7 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. The umbrella/overhead covering has a weighted base and any supports are not affixed to the sidewalk. Any support structures are of sufficient size and strength, made of durable materials, and free of defects Lighting and Electrical Connections Any lighting is outdoor rated, properly secured, and lightweight. Connection is directly connected to ground floor restaurant's power source and within the perimeter of the cafe. Does not extend beyond the perimeter of the sidewalk cafe. Does not extend beyond the perimeter of the sidewalk cafe. Does not extend beyond the perimeter of the sidewalk cafe. Does not extend beyond the perimeter of the sidewalk cafe. Does not extend to some the perimeter of the sidewalk cafe. Does not extend to any City property, including street trees.	Materials Checklist:				
Furnishings	Perimeter Demarcation Perimeter demarcation must be clear and visible by using a lightweight and removable self-supporting base wall, railing, planter, fence, or stanchion and rope. Maximum height is 2 feet 6 inches (excluding planting(s)).				
Lightweight and easily movable. Not affixed to the sidewalk. Awnings (Physically attached to the building) Minimum 8 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. Complies with the New York City Building Code and the requirements of the Landmarks Preservation Commission, as applicable. Overhead Coverings/ Umbrellas Minimum 7 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. The umbrella/overhead covering has a weighted base and any supports are not affixed to the sidewalk. Any support structures are of sufficient size and strength, made of durable materials, and free of defects Lighting and Electrical Connections Any lighting is outdoor rated, properly secured, and lightweight. Connection is directly connected to ground floor restaurant's power source and within the perimeter of the cafe. Does not extend beyond the perimeter of the sidewalk cafe. Does not exceed 10 feet in height. Not attached to any City property, including street trees.	*Optional- Only check the material categories you intend to use in your sidewalk cafe	<u>,*</u>			
Not attached to any City property, including street trees.	Lightweight and easily movable. Not affixed to the sidewalk. Awnings (Physically attached to the building) Minimum 8 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. Complies with the New York City Building Code and the requirements of the Landmarks P Commission, as applicable. Overhead Coverings/ Umbrellas Minimum 7 feet height from the ground and does not exceed 10 feet height. Easily removable, comprised of fire-grade and wind resistant materials. Does not extend beyond the perimeter of the sidewalk cafe. The umbrella/overhead covering has a weighted base and any supports are not affixed to Any support structures are of sufficient size and strength, made of durable materials, and Lighting and Electrical Connections Any lighting is outdoor rated, properly secured, and lightweight. Connection is directly connected to ground floor restaurant's power source and within the the cafe.	o the sidewalk. d free of defects.			
City Electrical Code.	Not attached to any City property, including street trees. Electrical work complies with the applicable requirements set forth in the DOT's rules and	d the New York			

Please check this box if you are submitting additional documents for review. Documents may include technical

drawings prepared by a licensed professional.