

RESTAURANT DETAILS

Food Service Establishment Permit(FSEP)

FSEP#: 50174263

Expiration Date: 08/04/2025

DOHMH Status: PENDING APPLICATION

Business Legal Name: TACO 94 U, LLC

Assumed Name: SANTO TACO

Business Address: 94 UNIVERSITY PLACE, NEW YORK, NY 10003

Venue Type: Restaurant (with bar)

Last updated from DOHMH: 10/14/2025

Restaurant Information

Entity Type: Limited Liability Corporation (LLC)

Phone: [REDACTED]

Email Address: [REDACTED]

Principal Place of Business Address

Address: 94 UNIVERSITY PLACE, NEW YORK, New York 10003

Email Address: [REDACTED]

DOS Information

DOS ID#: [REDACTED]

Process Name: The LLC

DOS Address: 21 Astor Place, New York, New York 10003

DOS Legal Name:

NYS Liquor Authority Information

NYSLA Serial No: 037025126241

License Type: On-Premises

Name of License: Taco 94 U LLC

Title of Representative: Attorney of Record

Name of Certificate Holder: Taco 94 U LLC

User Information

Created By: Max Bookman

Created On: 10/7/2025 10:31:49 AM

Business hours

Sun:

11:00 AM- 10:00 PM

Mon:

11:00 AM- 10:00 PM

Tues:

11:00 AM- 10:00 PM

Wed:

11:00 AM- 10:00 PM

Thurs:


11:00 AM- 10:00 PM

Fri:

11:00 AM- 10:00 PM


Sat:

11:00 AM- 10:00 PM



NEW YORK CITY
Eric Adams
 Mayor
Ylanis Rodriguez
 Commissioner

-  P1- Parking Space
 P2- Loading Area
 P3- Floating Parking



Applicant Name: Taco 94 U LLC

Restaurant Name: Santo Taco

FSEP Number: 50174263

- Symbols representing the approximate shape of the covering within the setup

- ☐ MANHOLE COVER
☐ UTILITY COVERING

SECTION 2: Required Clearances

- Please provide distances from the following objects.
- Only provide a distance if the listed object is within 15 feet of your proposed setup.
- Leave box blank if not applicable.
- Refer to the [Setup Guides](#) in the Dining Out NYC website for more information regarding clearances.

Elements with minimum 15 feet clearance from roadway cafe:

- ☐ R01- Subway Stair: Open End _____ feet
- ☐ R02- Fire Hydrant _____ feet

Elements with minimum 10 feet clearance from roadway cafe:

- ☐ R03- Subway Elevator Entrance _____ feet
- ☐ R04- FDNY Curb Cut _____ feet
- ☐ R05- MTA Curb Cut _____ feet

Elements with minimum 5 feet clearance from roadway cafe:

- ☐ R06- Curb Cut _____ feet ☐ R11- CitiBike/Bike Share Station _____ feet
- ☐ R07- Emergency Exit Hatch _____ feet ☐ R12- Bike Corral _____ feet
- ☐ R08- Subway Stair: Closed End _____ feet ☐ R13- Micromobility Station _____ feet
- ☐ R09- Subway Elevator: Non-Entry _____ feet ☐ R14- Drainage Infrastructure _____ feet
- ☐ R10- Bus Stop Pole: _____ feet
Non- Approaching Side

Elements with minimum 3 feet clearance from roadway cafe:

- ☐ R15- Elevated Train Infrastructure _____ feet
- ☐ R16- Transformer Vault _____ feet

Elements with minimum 1 foot and 6 inches clearance from roadway cafe:


- ☐ R17- Vent Infrastructure _____ feet

Elements with minimum 6 inches clearance from roadway cafe:

- ☐ R18- Thermoplastic Marking _____ feet

Roadway cafe distance from crosswalks:

- ☐ R19- Adjacent to non-approaching side of crosswalk (min. 8 foot distance) _____ feet
- ☒ R20- Adjacent to approaching (stopping) side of crosswalk (min. 20 foot distance) 20 feet
- ☐ R21- No crosswalk present (maintain 20 feet from curb line of intersecting street) _____ feet



SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the [Setup Guides](#) in the Dining Out NYC website for more information regarding materials.

Materials Checklist:

Required

☒ Barriers

- ☒ Maintained on all sides of the cafe except the side fronting the ground floor restaurant.
- ☒ Not permanently affixed to the roadway.
- ☒ 30-42 inches tall (excluding planting), and at least 4 inches in width.
- ☒ Barriers are interconnected with each other.
- ☒ Any cladding over the barriers is securely fastened or affixed.
- ☒ Minimum 4 inches wide reflective strip on each barrier on the outward facing side.
- ☒ Water-filled with a minimum of 150 pounds per linear foot of barrier length.
- ☐ If your proposed barriers will utilize fill materials other than water please check this box. This may require additional information from the applicant and further review by the Dining Out NYC team, as well as supporting DOT units and City agencies.

Optional- Only check the material categories you intend to use in your roadway cafe

☐ Flooring

- ☐ Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
- ☐ Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements.
- ☐ Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.

☐ Furnishings

- ☐ Lightweight and easily movable.

☐ Vertical Screenings

- ☐ Located between the barrier and 6 feet above the cafe base or floor.
- ☐ Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
- ☐ Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.
- ☐ If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

☐ Overhead Coverings/ Umbrellas

- ☐ Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe.
- ☐ Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
- ☐ Easily removable, comprised of fire-grade and wind resistant materials.
- ☐ If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

☐ Lighting and Electrical Connections

- ☐ Any lighting is outdoor rated, properly secured, and lightweight.
- ☐ At least 14 feet above sidewalk, and 18 feet above roadway.
- ☐ Not attached to any City property, including street trees.
- ☐ Electrical work complies with the applicable requirements set forth in the DOT's rules and the New York City Electrical Code.

- ☐ Please check this box if you are submitting additional documents for review. Documents may include technical drawings prepared by a licensed professional.