



JUN 24 2026

COMMUNITY BOARD 2 APPLICATION FOR A STATE LIQUOR AUTHORITY LICENSE

FOR EXISTING LICENSEES - ALTERATION TO ADD CONTIGUOUS OR NONCONTIGUOUS MUNICIPAL PUBLIC SPACE Form to be Completed and Returned with 30-Day Notice

Name/email of Principal/Contact: REHAN ALAM 
Name/email of Representative: MICHAEL KELLY 
Applicant/Premises Name: BLEECKER HOSPITALITY LLC
DBA Name: BOSCO
Address of Premises (include zip code): 169 BLEECKER STREET NY NY 10012
Cross Streets of Premises: THOMPSON + SULLIVAN STREET
License ID #: 0340-22-105148
☒ On Premise Liquor ☐ Restaurant Wine ☐ Tavern Wine ☐ Other _____

Sidewalk Café will have no more than (If premises is located on a corner please indicate for both streets):

_____ tables and _____ seats on _____ Street
_____ tables and _____ seats on _____ Street

Will applicant agree to close sidewalk café area by 10 PM every night? Yes ☐ No ☒

Will open sidewalk café area at _____

Roadbed / Open Streets will have no more than (If premises is located on a corner please indicate for both streets):

6 tables and 12 seats on SULLIVAN Street
5 tables and 10 seats on BLEECKER Street

Is roadbed in a floating parking lane separated from the curb by a bike path? Yes ☐ No ☒

Does DOT Dining Out NYC application include an FDNY waiver? Yes ☐ No ☒

Will applicant agree to close roadbed seating by 10 PM every night? Yes ☐ No ☒

Will open roadbed seating area at 10 AM

For all Applicants:

Will agree there will be no host stands, bus or service stations on the sidewalk or in the roadbed? Yes ☒ No ☐

Will agree there will be no exterior music, speakers or TVs? Yes ☒ No ☐

Will agree that all patrons in any sidewalk café or roadbed will be seated? Yes ☒ No ☐

SECTION 2: Required Clearances

- Please provide distances from the following objects:
- City provide a distance if the listed object is within 15 feet of your proposed setup. Leave box blank if not applicable.
- Refer to the [Safety Guidelines](#) in the Dining Out NYC website for more information regarding clearances.

Elements with minimum 15 feet clearance from roadway cafe:

- ☐ R01- Subway Sign: Open End _____ feet
- ☐ R02- Fire Hydrant _____ feet

Elements with minimum 10 feet clearance from roadway cafe:

- ☐ R03- Subway Elevator Entrance _____ feet
- ☐ R04- FONY Curb Cut _____ feet
- ☐ R05- MTA Curb Cut _____ feet

Elements with minimum 5 feet clearance from roadway cafe:

- ☐ R06- Curb Cut _____ feet ☐ R11- CitiBike Bike Share Station _____ feet
- ☐ R07- Emergency Exit Hatch _____ feet ☐ R12- Bike Corral _____ feet
- ☐ R08- Subway Sign: Closed End _____ feet ☐ R13- Micromobility Station _____ feet
- ☐ R09- Subway Elevator: Non-Entry _____ feet ☒ R14- Drainage Infrastructure 20+ _____ feet
- ☐ R10- Bus Stop Pole: _____ feet
- Non-Approaching Signs _____ feet

Elements with minimum 3 feet clearance from roadway cafe:

- ☐ R15- Elevated Train Infrastructure _____ feet
- ☐ R16- Transformer Vault _____ feet

Elements with minimum 1 foot and 6 inches clearance from roadway cafe:

- ☒ R17- Vent Infrastructure 8+ _____ feet

Elements with minimum 5 inches clearance from roadway cafe:

- ☒ R18- Thermoplastic Marking 6' _____ feet

Roadway cafe distance from crosswalks:

- ☒ R19- Adjacent to non-approaching side of crosswalk (min. 8 foot distance) 28' 11" _____ feet
- ☐ R20- Adjacent to approaching (stopping) side of crosswalk (min. 2.0 foot distance) _____ feet
- ☐ R21- No crosswalk present (maintain 20 feet from curb line of intersecting street) _____ feet



SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the [Safety Guidelines](#) in the Dining Out NYC website for more information regarding materials.

Materials Checklist:

Required*

Barriers

- ☒ Maintained on all sides of the cafe except the side fronting the ground floor restaurant.
- ☒ Not permanently affixed to the roadway.
- ☒ 30-42 inches tall (excluding planting), and at least 4 inches in width.
- ☒ Barriers are interconnected with each other.
- ☒ Any cladding over the barriers is securely fastened or affixed.
- ☒ Minimum 4 inches wide reflective strip on each barrier on the outward facing side.
- ☒ Water-filled with a minimum of 150 pounds per linear foot of barrier length.
- ☒ If your proposed barriers will utilize fill materials other than water, please check this box. This may require additional information from the applicant and further review by the Dining Out NYC team, as well as supporting DOT units and City agencies.

Optional: Only check the material categories you intend to use in your roadway cafe.

Flooring

- ☒ Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
- ☒ Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements.
- ☒ Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.

Furnishings

- ☒ Lightweight and easily movable.

Vertical Screenings

- ☒ Located between the barrier and 6 feet above the cafe base or floor.
- ☒ Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
- ☒ Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.
- ☒ If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

Overhead Coverings/ Umbrellas

- ☒ Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe.
- ☒ Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
- ☒ Easily removable, comprised of fire-grade and wind resistant materials.
- ☒ If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

Lighting and Electrical Connections

- ☒ Any lighting is outdoor rated, properly secured, and lightweight.
- ☒ At least 14 feet above sidewalk, and 18 feet above roadway.
- ☒ Not attached to any City property, including street trees.
- ☒ Electrical work complies with the applicable requirements set forth in the DO's rules and the New York City Electrical Code.

☐ Please check this box if you are submitting additional documents for review. Documents may include technical drawings prepared by a licensed professional.

SECTION 1: Site Plan


- This Site Plan Form is required to be uploaded in the "Roadway Site Plan" field of your online application
- Refer to the [How to Apply](#) page in the Dining Out NYC website for more information about the application process.

Identify Permitted Parking Location:

- Identify the Parking Sign in front of or around the area where your roadway setup would be located
- Roadway cafes can only be placed in:
 1. Parking spaces, which include metered and non-metered spaces commercial parking, alternate side parking, angled parking, and seasonally restricted parking
 2. Loading areas, including loading only truck loading, hotel loading, and no parking zones
 3. Floating Parking Lane - a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curb

- ☒ P1 - Parking Space
☐ P2 - Loading Area
☐ P3 - Floating Parking Lane

Use the space below to draw or upload your Site Plan representing your cafe, perimeters, furniture, and clearances.



Roadway Cafe Site Plan Form

BLEEKER MOSCOWITZ LLC

Applicant Name:

Bosco

Restaurant Name:

50119463

FSEP Number:

Drawing Requirements:

Food service establishment footage shown by:

- Line representing space occupied on building
- Labels
- Length

Street names:

- Labels on each street

Sidewalk shown as:

- Line representing street curb
- Width measured from building line to curb line

Roadway shown as:

- Lines indicating parking lane
- Width of parking lane

Cafe perimeter shown as:

- Lines indicating perimeter
- Length and width of all three sides

Set-up furniture (tables, chairs, etc.) shown as:

- Lines or symbols at approximate location within setup

Elements or objects shown as:

- Lines or symbols
- Labels
- Distance from cafe perimeter

Utility coverings shown as:

- Symbols representing the approximate shape of the covering with in the setup

- MANHOLE COVER
- UTILITY COVERING

SECTION 2: Required Clearances

- Please provide distances from the following objects:
- Only provide a distance if the listed object is within 15 feet of your proposed setup
- Leave box blank if not applicable.
- Refer to the [Dining Out NYC](#) website for more information regarding clearances.

Elements with minimum 15 feet clearance from roadway cafe:

- ☐ R01: Subway Stair Open End _____ feet
- ☐ R02: Fire Hydrant _____ feet

Elements with minimum 10 feet clearance from roadway cafe:

- ☐ R03: Subway Elevator Entrance _____ feet
- ☐ R04: FDM Curb Cut _____ feet
- ☐ R05: MTA Curb Cut _____ feet

Elements with minimum 5 feet clearance from roadway cafe:

- ☐ R06: Curb Cut _____ feet ☐ R11: Citi Bike Bike Share Station _____ feet
- ☐ R07: Emergency Exit Hatch _____ feet ☐ R12: Bike Corral _____ feet
- ☐ R08: Subway Stair Closed End _____ feet ☐ R13: Micro-mobility Station _____ feet
- ☐ R09: Subway Elevator Non-Entry _____ feet ☒ R14: Drainage Infrastructure _____ feet

- ☐ R10: Bus Stop Pole _____ feet
- ☐ Non-Approaching Side _____ feet

Elements with minimum 3 feet clearance from roadway cafe:

- ☐ R15: Elevated Train Infrastructure _____ feet
- ☐ R16: Transformer Vault _____ feet

Elements with minimum 1 foot and 6 inches clearance from roadway cafe:

- ☐ R17: Vent Infrastructure _____ feet

Elements with minimum 6 inches clearance from roadway cafe:

- ☐ R18: Thermoplastic Marking _____ feet

Roadway cafe distance from crosswalks:

- ☒ R19: Adjacent to non-approaching side of crosswalk (min 8 foot distance) 8 _____ feet
- ☐ R20: Adjacent to approaching (stopping) side of crosswalk (min 20 foot distance) _____ feet
- ☐ R21: No crosswalk present (maintain 20 feet from curb line of intersecting street) _____ feet



SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the [Dining Out NYC](#) website for more information regarding materials.

Materials Checklist:

- Barriers** *Required*
- ☒ Maintained on all sides of the cafe except the side fronting the ground floor restaurant.
 - ☒ Not permanently affixed to the roadway
 - ☒ 30-42 inches tall (excluding planting), and at least 4 inches in width
 - ☒ Barriers are interconnected with each other
 - ☒ Any cladding over the barriers is securely fastened or affixed
 - ☒ Minimum 4 inches wide reflective strip on each barrier on the outward facing side
 - ☒ Water-filled with a minimum of 150 pounds per linear foot of barrier length
 - ☒ If your proposed barriers will utilize fill materials other than water please check this box. This requires additional information from the applicant and further review by the Dining Out NYC team, as well as supporting DOT units and City agencies
- Flooring** *Optional: Only check the material categories you intend to use in your roadway cafe*
- ☒ Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
 - ☒ Flush with the curbline (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements
 - ☒ Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.
- Furnishings**
- ☒ Lightweight and easily movable.
- Vertical Screenings**
- ☒ Located between the barrier and 6 feet above the cafe base or floor.
 - ☒ Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe and is not affixed to the outward facing side of barriers.
 - ☒ Easily removable, comprised of non-opaque, fire-grade and wind resistant materials
 - ☒ If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.
- Overhead Coverings, Umbrellas**
- ☒ Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe
 - ☒ Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
 - ☒ Easily removable, comprised of fire-grade and wind resistant materials
 - ☒ If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.
- Lighting and Electrical Connections**
- ☒ Any lighting is outdoor rated, properly secured, and lightweight
 - ☒ At least 14 feet above sidewalk, and 18 feet above roadway
 - ☒ Not attached to any City property including street trees
 - ☒ Electrical work complies with the applicable requirements set forth in the DOT's rules and the New York City Electrical Code

Please check this box if you are submitting additional documents for review. Documents may include technical drawings prepared by a licensed professional.