



Eric Adams
Mayor

Ydanis Rodriguez
Commissioner

# COMMUNITY BOARD FEEDBACK PACKAGE

Please review this application and provide the required feedback.

Manhattan Community Board 4's (MCB4) recommendation is based on a voted at its May 7, 2025 Full Board Meeting with 38 members in favor of the recommendation, 0 member opposed, 1 members abstaining and 0 present but not eligible.

# **DINING OUT NYC**

## COMMUNITY BOARD RECOMMENDATION FORM

This form is to be used by community boards during the cafe review process. Any comments from the community board should be recorded on this form and submitted to NYC DOT. For information pertaining to specific cafe design requirements, visit the Dining Out NYC website for program legislation, rules, and Setup Guides.

Business Name: Mermaid Inn

**Cafe Location:** 227 10 AVENUE, NEW YORK, NY, 10011

Application Number: 20240802010088

CB Feedback Deadline (on date or next business day): 4/16/2025

NYCDOT Internal Use Only

Roadway Cafe Setup Comments:
Comments related to the cafe's <b>physical footprint and dimensions</b> :
Comments related to pedestrian flow (i.e., visbility, safety, potential crowding):
Comments related to potential conflicts with <b>existing curb use</b> (i.e., planters, bike racks, bus stops):
Overall recommendation for the cafe setup:
Suggested modifications related to the above referenced application:
Nelly Gonzalez 1/16/25

Community Board Authorizing Name

# **RESTAURANT DETAILS**

Food Service Establishment Permit(FSEP)

FSEP#: 50096675

Expiration Date: 08/31/2025 DOHMH Status: CURRENT

Business Legal Name: MERMAID CHELSEA LLC

Assumed Name: MERMAID INN

Business Address: 227 10 AVENUE, NEW YORK, NY 10011

Venue Type: Restaurant (with bar)

Last updated from DOHMH: 03/17/2025

**Restaurant Information** 

Entity Type: Limited Liability Corporation (LLC)

Phone: (212) 999-5939

Email Address: amanda@tminyc.com

DOS Information
DOS ID#: 5296392

Process Name: Mermaid Chelsea LLC

DOS Address: 227 10th, New York, New York 10011

NYS Liquor Authority Information NYSLA Serial No: 034021116830

License Type: On-Premises

Name of License: Mermaid Chelsea LLC Title of Representative: Managing Partner Name of Certificate Holder: Daniel Abrams

#### **Business** hours

Sun: 11:00 AM- 11:00 PM Mon: 4:30 PM- 11:00 PM Tues: 4:30 PM- 11:00 PM Wed: 4:30 PM- 11:00 PM Thurs: 4:30 PM- 11:00 PM Fri: 4:30 PM- 11:00 PM

Sat: 11:00 AM- 11:00 PM











# This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application Refer to the Flore to Apply page in the Dining Out NYC website for more information about the application process. Identify Permitted Parking Location: Identify the Parking Sign in front of or around the area where your roadway setup would be located Roadway cales can only be placed in. Parking spaces which include metered and non-metered spaces, commercial parking, alternate side parking, angled parking, and seasonally restricted parking and seasonally restricted parking only, truck loading, hotel loading, and no parking zones. Floating Parking Lane is a parking lane that is separated from the curb by a protected broycle lane that is adjacent to the curb P1- Parking Space P2- Loading Area P3- Floating Parking Lane Restaurant Footage = 40 ft Weight and Bike Lane Buffer

10th Avenue

Width of roadway cafe: 7:-4"

WIDTH OF ROADWAY CAFE = 8 FT

SECTION 1: Site Plan

Thermoplastic Marking

LENGTH OF ROADWAY CAFE = 25 F1

Length of roadway cafe



# Roadway Cafe Site Plan Form

Applicant Name: \_ Restaurant Name FSEP Number:

Drawing Requirements

### Food service establishment frontage

shown as Line representing the establishment's

- space facing the sidewalk
- Length

#### Street names:

Labels on each street

#### Sidewalk shown as:

Line representing street ourb

#### Roadway shown as:

Width of curbside lane

# Cafe perimeter shown as:

- Lines indicating perimeter
- · Length and width

# Set-up furniture (tables, chairs, etc.)

Lines or symbols at approximate location within setup

#### Elements (in Section 2 of this form) within 15 feet of cafe perimeter, shown

- Lines or symbols
- Distance from cafe perimeter
- Labels

#### Utility coverings (water/gas valves, and pull boxes) shown as:

Symbols representing the location within the setup

North arrow

SECTION 2: Required Clearan	ces	West To your		SECTION 3: Material Requirements
Please provide distances from the following objects. Only provide a distance if the listed object is within 15 feet of your proposed setup. Refer to the Setup Guides in the Dining Out NYC website for more information regarding clearances.				Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.  Refer to the Setup Guides in the Dining Out NYC website for more information regarding materials.
Elements with minimum 15 feet clearance from roadway cafe:				Materials Checklist:
R01=Subway Stair: Open End	feet	* R02- Fire Hydrant	15 feet	105 N 1989
Elements with minimum 10 feet o	learance from			*Required*  S Barriers (All of the following must be met)
R03- Subway Elevator Entrance	feet	R05- MTA Curb Cut	feet	Maintained on all sides of the cafe except the side fronting the ground floor restaurant
R04- FDNY Curb Cut	feet			X Not permanently affixed to the road way.     X 30.42 Inches tall (excluding planting), and at least 4 inches in width.     ■ 30.42 Inches tall (excluding planting).     ■ 30.42 Inches tall (excluding planting
Elements with minimum 5 feet clearance from roadway cafe:				Barriers are interconnected with each other
ROG- Curb Cut				Any cladding over the barriers is securely fasteried or affixed.
	feet	R11- CitiBike/Bike Share Station	feet	Minimum 4 inches wide reflective strip on each barrier on the outward facing side
R07- Emergency Exit Hatch	fcel	R12- Bike Corral	feet	☑ Water-filled with a minimum of 150 pounds per linear foot of barrier length
R08- Subway Stair: Closed End	fcet	R13- Micromobility Station	feet	
R09- Suhway Elevator: Non-Entry	feet	R14- Drainage Infrastructure	feet	*Optional - Only check the material categories you intend to use in your roadway cafe*
R10- Bus Stop Pale:				Elooring (if using, all of the following must be met)
	feet			Durable, lightweight, easily removable, mold-resistant, elevated from the current level to allow fre-
Elements with minimum 3 feet cl	earance from r	oadway cafe:		Grainage, and removable to allow for cleaning.
R15 - Elevated Train Infrastructure	feet	R16- Transformer Vault	feet	Flush with the curb line (except if located on a slope, be flush to the greatest extent (easible), and compliant with applicable accessibility requirements.
Elements with minimum 1 foor ar	nd 6 inches cle	arance from roadway cafe:		Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.
817- Vent Infrastructure. Utility vent poles, vent	feeı	R1B- Manholes	inches	Furnishings (if using, all of the following must be met)  Suightweight and easily movable.
grates, subway grates				Vertical Screenings (it using, all of the following must be met)
Elements with minimum 6 inches clearance from roadway cate:  (A19 Thermoplastic Marking 0.5 feet				□ Located between the barrier and 6 feet above the cafe base or floor. □ Located on the roadway lacing side, sloes not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
The thickney	0.5 feet			Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials
Roadway cafe distance from cros	swalks:			If within 50 leet of any regulatory or warming signs, does not exceed 46 inches in height.
				Querhead Coverings/ Umbrellas (if using, all of the following must be met)
R20 Adjacent to non-approaching side of				Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe
crosswalk (min 8 foot distance)	feet		stance required m crosswalk on	<ul> <li>Has a weighted base and any support structures are not affixed to the outward facing aide of barriers, are of sufficient size and strength, made of durable materials, and free of defects</li> </ul>
R21- Adjacent to		non-approaching side	prosching side	If any removable, comprised of fire-grade and wind quistant practicals
approaching (stopping)		× 1:		☐ If within 50 feet of any regulatory or warning signs, does not receed 46 inches in height
side of crosswalk (min_20 (oot distance)	feet	34	inden!	Lighting and Electrical Connections (if using, all of the following must be met)
(mini_20 tout distance)	reet	Electric .	200	At least 14 feet above sidewalk, and 18 feet above roadway.
L. J R22 No crosswalk present		000	TOTAL I	Not attached to any City property, including street trees
(maintain 20 feet from curb line of intersecting street)	feet			Electrical work complies with the applicable requirements set forth in DOT's rules and the New York City  Electrical Code. Please note that this may require additional permits from DOB or FDNY, and/or approval from the  Landmanks Preservation Commission (LPC) as applicable.
Check this box if none of the ob	jects listed abov	e are within 15 feet of the proposed set	ир.	1